

Single Inverter

General Description

The ET74LVC1G04 is an inverter operating from a 1.65V to 5.5V supply. This device is fabricated with advanced CMOS technology to achieve ultra-high speed with high output drive.


Features

- Tiny SC70-5, SOT23-5, DFN6(1.0×1.5), DFN6(1.0×1.0) Packages
- 24mA Sink and Source Output Capability
- Over-Voltage Tolerant Inputs and Outputs
- Designed for 1.65V to 5.5V VCC Operation
- These Devices are Pb-Free and are RoHS Compliant
- MSL1 (DFN6) , MSL3(SC70-5,SOT23-5)

Device Information

Part No.	Package	Size
ET74LVC1G04	SC70-5	1.3mm×2.1mm
ET74LVC1G04T	SOT23-5	1.6mm×2.9mm
ET74LVC1G04Y	DFN6	1.0mm×1.5mm
ET74LVC1G04N	DFN6	1.0mm×1.0mm

Pin Configuration



ET74LVC1G04

Pin Function


SC70-5/ SOT23-5

Pin No.	Pin Name	Function
1	NC	No connect
2	A	Input
3	GND	Ground
4	Y	Output
5	VCC	Supply Voltage

DFN6

Pin No.	Pin Name	Function
1	NC	No connect
2	A	Input
3	GND	Ground
4	Y	Output
5	NC	No connect
6	VCC	Supply Voltage

Block Diagram



Function Table

Input A	Output Y
L	H
H	L

ET74LVC1G04

Absolute Maximum Ratings

Symbol	Parameter		Value	Unit
V_{CC}	DC Supply Voltage		-0.5 to 7.0	V
V_I	DC Input Voltage ⁽¹⁾		$-0.5 \leq V_I \leq +7.0$	V
V_O	DC Output Voltage Output in Higher or Low State		-0.5 to $V_{CC} + 0.5$	V
I_{IK}	DC Input Diode Current	$V_I < GND$	-50	mA
I_{OK}	DC Output Diode Current	$V_O < GND, V_O > V_{CC}$	± 50	mA
I_O	DC Output Sink Current		± 50	mA
I_{CC}	DC Supply Current per Supply Pin		± 100	mA
I_{GND}	DC Ground Current per Supply Pin		± 100	mA
T_{STG}	Storage Temperature Range		-65 to 150	°C
T_L	Lead Temperature, Soldering 10 Seconds		260	°C
T_J	Max Junction Temperature		150	°C
V_{ESD}	ESD Classification	Human Body Model ⁽²⁾	± 4000	V
		Charged Device Model ⁽³⁾	± 1000	
I_{LU}	Max Latch up Current Above V_{CC} and GND at 125°C ⁽⁴⁾		± 100	mA

Stresses exceeding those listed in this table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.

Note1. IO absolute maximum rating must be observed.

Note2. Tested to EIA/JESD22-A114-A.

Note3. Tested to JESD22-C101-A.

Note4. Tested to EIA/JESD78.

Thermal Characteristics

Symbol	Package	Ratings	Value	Unit
$R_{\theta JA}$	SC70-5	Thermal Characteristics, Thermal Resistance, Junction-to-Air	300	°C /W
	SOT23-5		250	
	DFN6(1.0×1.5)		440	
	DFN6(1.0×1.0)		440	
P_D	SC70-5	Power Dissipation in Still Air at 85°C	215	mW
	SOT23-5		260	
	DFN6(1.0×1.5)		150	
	DFN6(1.0×1.0)		150	

ET74LVC1G04

Recommended Operating Conditions

Symbol	Parameter		Min	Max	Unit
V _{CC}	DC Supply Voltage		1.65	5.5	V
	Operating Date Retention		1.5	5.5	
V _{IN}	DC Input Voltage		0	5.5	V
V _{OUT}	DC Output Voltage(High or Low State)		0	5.5	V
T _A	Operating Temperature Range		-40	125	°C
t _r ,t _f	Input Rise and Fall Time	V _{CC} = 2.5 V ± 0.2 V	0	20	ns/V
		V _{CC} = 3.0 V ± 0.3 V	0	10	
		V _{CC} = 5.0 V ± 0.5 V	0	5	

Electrical Characteristics

DC Electrical Characteristics

Symbol	Parameter	Condition	V _{CC} (V)	T _A = 25 °C			-40°C ≤ T _A ≤ 125°C		Unit
				Min	Typ	Max	Min	Max	
V _{IH}	High-Level Input Voltage		1.65 to 1.95 2.3 to 5.5	0.75V _{CC} 0.7V _{CC}			0.75V _{CC} 0.7V _{CC}		V
V _{IL}	Low-Level Input Voltage		1.65 to 1.95 2.3 to 5.5			0.25V _{CC} 0.3V _{CC}		0.25V _{CC} 0.3V _{CC}	V
V _{OH}	High-Level Output Voltage	I _{OH} = -100uA	1.65 to 5.5	V _{CC} -0.1	V _{CC}		V _{CC} -0.1		V
		I _{OH} = -3mA	1.65	1.29	1.4		1.29		
		I _{OH} = -8mA	2.3	1.9	2.1		1.9		
		I _{OH} = -12mA	2.7	2.2	2.4		2.2		
		I _{OH} = -16mA	3.0	2.4	2.7		2.4		
		I _{OH} = -24mA	3.0	2.3	2.5		2.3		
		I _{OH} = -32mA	4.5	3.8	4.0		3.8		
V _{OL}	Low-Level Output Voltage	I _{OH} = 100uA	1.65 to 5.5		0.0	0.1		0.1	V
		I _{OL} = 3mA	1.65		0.08	0.24		0.24	
		I _{OL} = 8mA	2.3		0.20	0.3		0.3	
		I _{OL} = 12mA	2.7		0.22	0.4		0.4	
		I _{OL} = 16mA	3.0		0.28	0.4		0.4	
		I _{OL} = 24mA	3.0		0.38	0.55		0.55	
		I _{OL} = 32mA	4.5		0.42	0.55		0.55	
I _{IN}	Input Leakage Current	V _{IN} = 5.5V or GND	0 to 5.5		±0.1			±1.0	μA

ET74LVC1G04

I_{OFF}	Power Off Leakage Current	$V_{IN}=5.5V$ or $V_{OUT} = 5.5V$	0			1		10	μA
I_{CC}	Quiescent Supply Current	$V_{IN} = 5.5V$ or GND	5.5					10	μA

AC Electrical Characteristics

$t_r = t_f = 2.5ns$; $C_L = 50pF$; $R_L = 500 \Omega$

Symbol	Parameter	Condition	$V_{CC}(V)$	$T_A = 25^\circ C$			$-40^\circ C \leq T_A \leq 125^\circ C$		Unit
				Min	Typ	Max	Min	Max	
t_{PLH} t_{PHL}	Propagation Delay (Figure3 and4)	$R_L = 1M\Omega, C_L = 15pF$	1.65	2.0	5.3	11.4	2.0	12.0	ns
			1.8	2.0	4.4	9.5	2.0	10.0	
		$R_L = 1M\Omega, C_L = 15pF$	2.5 ± 0.2	0.8	3.0	6.5	0.8	7.0	
		$R_L = 1M\Omega, C_L = 15pF$	3.3 ± 0.3	0.5	2.4	4.5	0.5	4.7	
		$R_L = 500\Omega, C_L = 50pF$		1.5	2.5	5.5	1.5	5.2	
		$R_L = 1M\Omega, C_L = 15pF$	5.0 ± 0.5	0.5	2.0	3.9	0.5	4.1	
		$R_L = 500\Omega, C_L = 50pF$		0.8	2.4	4.3	0.8	4.5	

Capacitive Characteristics

Symbol	Parameter	Condition	Typ	Unit
C_{IN}	Input Capacitance	$V_{CC} = 5.5V, V_I = 0V$ or V_{CC}	>2.5	pF
C_{PD}	Power Dissipation Capacitance ⁽⁵⁾	10MHz, $V_{CC} = 3.3V, V_I = 0V$ or V_{CC}	26	pF
		10MHz, $V_{CC} = 5.5V, V_I = 0V$ or V_{CC}	30	

Note5. C_{PD} is defined as the value of the internal equivalent capacitance which is calculated from the operating current consumption without load. Average operating current can be obtained by the equation: $I_{CC(OPR)} = C_{PD} \times V_{CC} \times f_{in} + I_{CC} \times C_{PD}$ is used to determine the no-load dynamic power consumption; $P_D = C_{PD} \times V_{CC}^2 \times f_{in} + I_{CC} \times V_{CC} \times Fig.$




Figure 3. Switching Waveform





Figure4. Test Circuit

ET74LVC1G04

Package Dimension

SC70-5




COMMON DIMENSIONS
(UNITS OF MEASURE=MILLIMETER)

SYMBOL	MIN	NOM	MAX
A	0.85	--	1.05
A1	0	--	0.10
A2	0.80	0.90	1.00
A3	0.47	0.52	0.57
b	0.23	--	0.33
c	0.12	--	0.18
D	2.02	2.07	2.12
E	2.20	2.30	2.40
E1	1.25	1.30	1.35
e	0.60	0.65	0.70
L	0.28	0.33	0.38
L1	0.50REF		
L2	0.15BSC		
R	0.10	--	--
R1	0.10	--	0.25
θ	0°	--	8°
θ_1	6°	9°	12°
θ_2	6°	9°	12°

ET74LVC1G04

SOT23-5




COMMON DIMENSIONS
(UNITS OF MEASURE=MILLIMETER)

SYMBOL	MIN	NOM	MAX
A	--	--	1.25
A1	0	--	0.15
A2	1.00	1.10	1.20
A3	0.60	0.65	0.70
b	0.36	--	0.50
c	0.14	--	0.20
D	2.826	2.926	3.026
E	2.60	2.80	3.00
E1	1.526	1.626	1.726
e	0.90	0.95	1.00
L	0.35	0.45	0.60
L1	0.59REF		
L2	0.25BSC		
R	0.10	--	--
R1	0.10	--	0.25
θ	0°	--	8°
θ1	3°	5°	7°
θ2	6°	--	14°

ET74LVC1G04

DFN6(1.0×1.5)




COMMON DIMENSIONS
(UNITS OF MEASURE=MILLIMETER)

SYMBOL	MIN	NOM	MAX
A	0.50	--	0.60
A1	0	0.02	0.05
A3	0.10REF		
b	0.15	0.20	0.25
D	0.90	1.00	1.10
E	1.40	1.50	1.60
e	0.40	0.50	0.60
H	0.10REF		
L	0.30	0.35	0.40
L1	0.35	0.40	0.45

ET74LVC1G04

DFN6(1×1)



COMMON DIMENSIONS
(UNITS OF MEASURE=MILLIMETER)

SYMBOL	MIN	NOM	MAX
A	0.34	0.37	0.40
A1	0	0.02	0.05
A3	0.10REF		
b	0.10	0.15	0.20
D	0.95	1.00	1.05
E	0.95	1.00	1.05
e	0.30	0.35	0.40
H	0.10REF		
K	0.15	--	--
L	0.35	0.40	0.45
L1	0.35	0.40	0.45
L2	0.075REF		

ET74LVC1G04

Revision History and Checking Table

Version	Date	Revision Item	Modifier	Function & Spec Checking	Package & Tape Checking
1.0	2017-07-19	Original Version	Ma Yong jian	Ma Yong jian	Ma Yong jian
1.1	2021-06-25	Update DC/AC Table	Ma Yong jian	Ma Yong jian	Ma Yong jian
1.2	2022-05-18	Add DFN6(1X1)	Shibo	Shibo	Shibo
1.3	2022-06-10	ESD Update	Shibo	Shibo	Shibo
1.4	2022-08-03	Update DFN6(1X1)	Shibo	Shibo	Shibo
1.5	2022-10-14	Update format and Thermal Characteristics	Wuhan	Shibo	Shibo
1.6	2023-11-30	Update Pin table/ESD	Shibo		