

High Input, Ultra-low Noise, Low IQ 500mA LDO

General Description

The ET55HS24XX is a low-dropout linear regulator (LDO) designed for 2.5V to 20V power supplies, delivering a maximum output current of 500mA. Featuring high power rejection ratio and low noise characteristics, making it ideal for powering high-performance analog and mixed-signal circuits. The device employs an advanced circuit architecture and unique processing technology, with both C_{IN} and C_{OUT} requiring only a compact 2.2uF ceramic output capacitor to achieve excellent transient response performance for both lines and loads.

Features

- Wide Input Voltage Range: 2.5V to 20V
- Adjust Output Voltage Range: 1.2V to $V_{IN} - 1V$
- Fixed Output Voltage Versions: 3.3V (only ET55HS2433Y) and 5.0V (only ET55HS2450Y)
- Low Static Current: 50uA (Typical)
- Low Turn-off Current: 1.2uA
- Ultra-low Noise: 10uVrms (Typical) @10mA
- High Power Supply Rejection Ratio (PSRR)
 - 91dB @ 10kHz
 - 70dB @ 100kHz
 - 60dB @ 1MHz
- Output Current: 500mA
- Output Voltage Accuracy: $\pm 1\%$
- Low Dropout Voltage:
 - 20mV @ 10mA
 - 250mV @ 200mA
 - 700mV @ 500mA
- Internal Soft Start
- Precision-enable Control
- Reverse Input Protection
- Available in Various Packages including SOP8, DFN6 (2mm × 2mm), and SOT23-5

Application

- Suitable for Noise-sensitive Applications such as ADCs, DACs, and Precision Amplifiers.
- Communications and Infrastructure
- Health Care
- Industry and Instrumentation

ET55HS24XX

Device Information

Part No.	Package	Packing Option	MSL
ET55HS24ADJM	SOP8	Tape and Reel, 4K/Reel	3
ET55HS24ADJY	DFN6 (2mm × 2mm)	Tape and Reel, 3K/Reel	1
ET55HS24XXY	DFN6 (2mm × 2mm)	Tape and Reel, 3K/Reel	1
ET55HS24ADJY1	DFN6 (2mm × 2mm)	Tape and Reel, 3K/Reel	1
ET55HS24ADJ	SOT23-5	Tape and Reel, 3K/Reel	3
ET55HS24ADJT	SOT23-5	Tape and Reel, 3K/Reel	3

Pin Configuration





Figure1. Pin Configuration

ET55HS24XX

Pin Function

SOP8	DFN6		SOT23-5		Pin Name	Pin description
	Y	Y1	/	T		
1	1	1	5	5	OUT	Output Voltage Port Pin. Requires a bypass capacitor of 2.2 μ F or larger to connect OUT to GND.
2	2	2	4	4	ADJ	Detect Input Pin. Connect to the load side, and use an external resistor divider to set the output voltage higher than the fixed output voltage
3,6	3	3	2	2	GND	Ground Pin.
5	4	4	3	/	EN	Enable the Pin: Set EN high to activate the voltage regulator, set EN low to deactivate it, and connect EN to IN for automatic startup.
8	6	6	1	1	IN	The Voltage Regulator's Input Power Pin. Should be bypassed to GND using a 2.2 μ F or larger capacitor.
4,7	5	/	/	/	SS	Soft Start Time Adjustment Pin. External capacitors with different capacitance values can adjust the soft start time.
/	/	5	/	3	NC	No Connection.
9					EP	Heat Dissipation Pin. Since EP pads are electrically connected to the internal GND, it is recommended to connect to the GND layer.

Block Diagram



ET55HS24XX

Functional Description

Input Bypass Capacitor

The input capacitor should be at least 2.2uF and placed as close to the chip as possible to minimize PCB traces' impact on the circuit. If the output capacitor exceeds 2.2uF, increase the input capacitor value accordingly.

Output Capacitance

The ESR of the output capacitor impacts the stability of the LDO control loop. To ensure stable chip operation, a 2.2uF output capacitor with ESR below 0.3Ω and ESL under 2nH is recommended. Additionally, the output capacitor affects the transient response to load current variations. For applications requiring high transient response or significant load current fluctuations, using a larger capacitance value is advised to enhance the transient response of the ET55HS24XX.

Input and Output Capacitance Characteristics

Input/output capacitors must maintain proper operation within the specified temperature range and under DC bias conditions. X5R or X7R dielectric capacitors are recommended. Y5V and Z5U dielectric capacitors have poor temperature and current bias characteristics and are not recommended.

Current Limit and Over-thermal Protection

The chip incorporates current limiting and thermal overload protection circuits to prevent damage caused by excessive power consumption. When the output current exceeds 630mA (typical value), the chip enters current limiting protection mode, reducing the output voltage. If the junction temperature surpasses 150°C, the chip activates its overheat protection function, temporarily shutting down the output. When the junction temperature drops below 130°C, the overheat protection is deactivated, and the chip resumes output. Notably, a short circuit causes intense heat generation, triggering the overheat protection when junction temperature exceeds 150°C. If the short circuit issue isn't resolved promptly, the chip will re-enter current limiting protection mode and activate overheat protection again upon temperature recovery, creating a recurring cycle until the fault is cleared. To ensure stable operation, external power consumption must be controlled to keep junction temperature below 150°C.

Soft Start

The ET55HS24XX features a voltage-controlled soft-start function with an external capacitor (SS pin). This capability is crucial for eliminating power-on initialization issues in scenarios where the device drives FPGAs, DSPs, or other processors. By controlling the output voltage ramp, the peak inrush current during startup is reduced, thereby minimizing transient effects on the input power bus. The soft-start ramp time depends on the soft-start current (I_{SS}) and soft-start capacitor (C_{SS}), which can be calculated using [Equation1](#):

$$T_{SS} = 500\mu s + (C_{SS} \text{ pF} / I_{SS} \mu A) \quad (1)$$

The I_{SS} is the soft-start charging current, which is 0.787uA.

The 500us in Equation1 represents the initial soft-start time without ADJ mode. When using ADJ mode to adjust the output voltage, this initial time should be recalibrated based on actual measured values. The C_{SS} must be a low-leakage current capacitor, preferably made of X7R, X5R, or C0G dielectric materials. When this feature is disabled, the SS pin remains floating, resulting in an initial soft-start time of approximately 442us for the output voltage.

ET55HS24XX

Enable and Disable Operations

Under normal operating conditions, the ET55HS24XX uses the EN pin to enable or disable the output voltage. When EN is high, V_{OUT} is activated; when EN is low, V_{OUT} is deactivated. For automatic startup, connect EN to IN.

Output Voltage Adjustment Principle

The adjustable output voltage version allows voltage adjustment through external voltage divider resistors (the maximum output voltage is limited by device characteristics). The voltage adjustment principle is shown in [Equation2](#), where R1 and R2 are the resistors in the output voltage divider, and V_{REF} = 1.2V.

$$V_{OUT} = V_{REF} \times (1 + R1 / R2) \quad (2)$$

Adjustable Output Voltage Device Applications

The ET55HS24XX model list includes the ADJ variant, which uses 1.2V as its reference voltage for ADJ adjustment. For higher output voltage requirements in practical applications, simply select an appropriate voltage divider resistor. For example, to achieve 6V output voltage, use V_{REF} = 1.2V as specified in [Equation2](#).

If R1 is 200K, R2 can be set to 50K.

The calculation is as follows:

$$V_{OUT} = 1.2 \times (1 + 200K / 50K) = 6V$$

Fixed Output Voltage Device Applications

The ET55HS24XX model list includes devices with fixed output voltage. Refer to the model selection list.

If you need to adjust the fixed output voltage in practical applications, simply refer to [Equation1](#). Here is a calculation example:

For fixed 5V output, to achieve 6V output voltage, use 5V reference voltage (V_{REF}) according to [Equation2](#). Select 40kΩ resistor (R1) and 200kΩ resistor (R2).

$$6V = 5V \times (1 + 40K / 200K)$$

Recommendations for R1 and R2 component selection: It is recommended to keep R2 below 200kΩ to minimize output voltage errors caused by ADJ pin input current. Additionally, connecting a 100nF feedforward capacitor (C_{FF}) in parallel with R1 helps reduce output voltage noise and PSRR in ADJ mode. For example, when both R1 and R2 are 200kΩ and the default output voltage is 1.2V, the adjustable output voltage can reach 2.4V. Assuming a typical ADJ pin input current of 2nA at 25°C, the output voltage error caused by this current is 0.2mV (0.016%).

ET55HS24XX

Absolute Maximum Ratings

Symbol	Parameters	Range	Unit
V _{IN}	Input Voltage	-20 to 20	V
V _{OUT}	Output Voltage	-0.3 to V _{IN}	V
V _{EN}	Enable Pin Voltage	-0.3 to V _{IN}	V
V _{ADJ}	ADJ Pin Voltage	-0.3 to 5.5	V
T _{JMAX}	Maximum Junction Temperature Range	150	°C
T _{STG}	Storage Temperature	-50 to 150	°C

Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.

Note1: Refer to Electrical Characteristics and Application Information for Safe Operating Area and IN port needs to be powered on before the EN port.

Thermal Performance

Thermal Resistance	SOP8	DFN6	SOT23-5	Unit
R _{θJA}	113.9	100	182	°C /W
R _{θJC}	54.7	77	70	°C /W

The PCB's layered structure, copper foil thickness, device thermal pads, and the number and diameter of vias near components all influence thermal characteristics. These factors should be evaluated based on actual application requirements.

The thermal resistance coefficient of SOP8 shown in the table is based on a PCB with dimensions of 115×76cm (length × width), a thickness of 1.6mm, a 4-layer board, and a copper ratio of 20%,100%,100%, and 5% for L1 to L4 respectively, with a copper thickness of 1 ounce for each layer.

Recommended Operating Conditions

Symbol	Parameters	Range	Unit
V _{IN}	Input Voltage	2.5 to 20	V
I _{OUT}	Output Voltage	0 to 500	mA
T _J	Operating Junction Temperature Range	-40 to 125	°C
C _{IN}	Enter the Effective Capacitance of the Ceramic Capacitor	> 1.5	μF
C _{OUT}	Output the Effective Capacitance of the Ceramic Capacitor	> 1.5	μF
ESR	Equivalent Series Resistance of Input/Output Capacitors	5 to 100	mΩ

ET55HS24XX

Electrical Characteristics

Unless otherwise noted, ($V_{IN} = V_{OUT} + 1V$) or 5V, $V_{OUT} = 3.3V$, $I_{OUT} = 10mA$, $C_{IN} = C_{OUT} = 2.2\mu F$, $T_A = 25^\circ C$.

Symbol	Parameter	Test Conditions ⁽⁶⁾	Min	Typ	Max	Unit
V_{IN}	Input Voltage Operation Range		2.5		20	V
I_{Q_ON}	DC Supply Quiescent Current	$I_{OUT} = 0mA$		50		μA
I_{GND}	GND Current	$I_{OUT} = 10mA$		140		μA
		$I_{OUT} = 500mA$		2		mA
I_{Q_OFF}	DC Supply Shutdown Current	EN = GND		1.2		μA
V_{OUT}	Regulated Output Voltage		-1		1	%
I_{OUT}	Output Current			500		mA
REG _{LINE}	Output Voltage Line Regulation	$V_{IN} = (V_{OUT} + 1V)$ to 20V		0.002		%/V
REG _{LOAD}	Output Voltage Load Regulation ⁽²⁾	$I_{OUT} = 100\mu A$ to 500mA		0.002		%/mA
V_{DROP}	Dropout Voltage ⁽³⁾	$I_{OUT} = 10mA$		20		mV
		$I_{OUT} = 200mA$		250		mV
		$I_{OUT} = 500mA$		700		mV
t_{ON}	Soft-start Time ⁽⁴⁾	From $V_{EN} > V_{ENH}$ to $V_{OUT} = 90\%$ of $V_{OUT(NOM)}$		356		μs
I_{LIMIT}	Current Limit ⁽⁵⁾			630		mA
V_{UVLO_R}	Under-Voltage Lockout, Rise			2.5		V
V_{UVLO_F}	Under-Voltage Lockout, Fall			2.2		V
V_{UVLO_HYS}	Under-voltage Threshold Hysteresis			300		mV
V_{ENH}	EN Input Logic Low Voltage	$2.5V \leq V_{IN} \leq 20V$		1.2	1.3	V
V_{ENL}	EN Input Logic High Voltage	$2.5V \leq V_{IN} \leq 20V$		1.1		V
V_{EN-HYS}	EN Input Logic Threshold Hysteresis	$2.5V \leq V_{IN} \leq 20V$		120		mV
t_{DON}	EN Input Delay Time	From $V_{EN} > 0V$ to $V_{OUT} = 10\%$ of $V_{OUT(NOM)}$		80		μs
e_N	Output Noise Voltage	$f = 10Hz$ to 100KHz		10		μV_{RMS}

ET55HS24XX

Electrical Characteristics (Continued)

Unless otherwise noted, ($V_{IN} = V_{OUT} + 1V$) or 5V, $V_{OUT} = 3.3V$, $I_{OUT} = 10mA$, $C_{IN} = C_{OUT} = 2.2\mu F$, $T_A = 25^\circ C$

Symbol	Parameter	Test Conditions ⁽⁶⁾	Min	Typ	Max	Unit
PSRR	Power Supply Rejection Ratio	$I_{OUT} = 10mA$, $f = 10kHz$, $V_{IN} = 5V$, $V_{OUT} = 3.3V$		90		dB
		$I_{OUT} = 10mA$, $f = 100kHz$, $V_{IN} = 5V$, $V_{OUT} = 3.3V$		70		dB
		$I_{OUT} = 10mA$, $f = 1MHz$, $V_{IN} = 5V$, $V_{OUT} = 3.3V$		60		dB
t_{SS}	Soft Start	C_{SS} Float, $I_{SS} = 0.787\mu A$ $t_{SS} = (500\mu s) + (C_{SS} pF) / (I_{SS} \mu A)$ From $V_{EN} > V_{ENH}$ to $V_{OUT} = 90\%$ of $V_{OUT(NOM)}$		442		μs
T_{SD}	Over-temperature Shutdown Threshold	T_J Rising		150		$^\circ C$
T_{HYS}	Over-temperature Shutdown Hysteresis	T_J Falling from Shutdown		15		$^\circ C$

Note2: Calculated based on the endpoint using 100uA and 500mA load.

Note3: The voltage difference is defined as the voltage difference between the input and output when the input voltage is set to the nominal output voltage. The voltage difference is only applicable to output voltages above 2.5V.


Note4: The start time is defined as the duration from the rising edge of EN to when OUT reaches 90% of its nominal value.

Note5: The current limit threshold is defined as the current at which the output voltage drops to 90% of the rated typical value. For example, the current limit for a 5.0V output voltage is defined as the current that causes the output voltage to drop to 90% of 5.0V, or 4.5V.


Note6: Under all operating conditions, input and output capacitors must be at least 1.5uF. When selecting components, consider all application conditions to ensure minimum capacitance requirements. For any LDO, use X7R/X5R capacitors instead of Y5V/Z5U capacitors.

ET55HS24XX

Application Circuits



ET55HS24XXY with Fixed Output Voltage Circuit




ET55HS24ADJ with Adjustable Output Voltage Circuit

Figure3. Application Circuits

ET55HS24XX


Typical Characteristics

$V_{IN} = (V_{OUT} + 1V)$ or $2.5V$ (the higher value), $V_{REF} = V_{IN}$, $I_{OUT} = 10mA$, $C_{IN} = C_{OUT} = 2.2\mu F$, $T_A = 25^\circ C$, temperature curve test based on T_J , unless otherwise specified




Line Transient

($V_{IN} = 3.7\sim 4.7V$, $V_{OUT} = 1.2V$, $I_{OUT} = 500mA$)




Line Transient

($V_{IN} = 4\sim 5V$, $V_{OUT} = 3V$, $I_{OUT} = 500mA$)




Load Transient

($V_{OUT} = 1.2V$, $I_{OUT} = 10\sim 500mA$)




Load Transient

($V_{OUT} = 3V$, $I_{OUT} = 10\sim 500mA$)




PSRR($I_{OUT} = 10mA$)




PSRR($V_{IN} = 3V$)





ET55HS24XX




Output Noise PSD









T_{ON}



ET55HS24XX




ET55HS24XX



ET55HS24XX

Package Dimension

SOP8




(Unit: mm)

Unit Symbol	MIN	NOM	MAX	Unit Symbol	MIN	NOM	MAX
A	-	-	1.65	E	5.80	6.00	6.20
A1	0.05	-	0.15	E1	3.80	3.90	4.00
A2	1.30	1.40	1.50	E2	2.21 REF		
A3	0.60	0.65	0.70	e	1.27 BSC		
b	0.39	-	0.47	e1	0.10 REF		
b1	0.38	0.41	0.44	h	0.25	-	0.50
c	0.20	-	0.24	L	0.50	0.60	0.80
c1	0.19	0.20	0.21	L1	1.05 REF		
D	4.80	4.90	5.00	θ	0°	-	8°
D1	3.10 REF						

ET55HS24XX

DFN6 (2mm × 2mm)




(Unit: mm)

Unit Symbol	MIN	NOM	MAX	Unit Symbol	MIN	NOM	MAX
A	0.70	0.75	0.80	E	1.90	2.00	2.10
	0.85	0.90	0.95	E2	0.90	1.00	1.10
A1	-	0.02	0.05	e	0.65 BSC		
b	0.25	0.30	0.35	h	0.15	0.20	0.25
c	0.18	0.20	0.25	L	0.20	0.25	0.30
D	1.90	2.00	2.10	Nd	1.30 BSC		
D2	1.50	1.60	1.70	K	0.20	-	-

ET55HS24XX

SOT23-5




(Unit: mm)

Unit Symbol	MIN	NOM	MAX	Unit Symbol	MIN	NOM	MAX
A	-	-	1.25	D	2.82	2.92	3.02
A1	0.04	-	0.10	E	2.60	2.80	3.00
A2	1.00	1.10	1.20	E1	1.50	1.60	1.70
A3	0.60	0.65	0.70	e	0.95 BSC		
b	0.33	-	0.41	e1	1.90 BSC		
c	0.15	-	0.19	L	0.30	-	0.60
c1	0.14	0.15	0.16	θ	0°	-	8°


ET55HS24XX

Tape and Reel Information

SOP8




DFN6 (2mm× 2mm)



ET55HS24XX

SOT23-5



Revision History and Checking Table

Version	Date	Revision Item	Modifier	Function & Spec Checking	Package & Tape Checking
0.0	2020-07-08	Original Version	Wang peng	Liu xiaomin	Liu jiaying
1.0	2024-11-02	Official Version	Yang xiaoxu	Liu xiaomin	Liu jiaying
1.0.a	2026-01-12	Update Format	Xu tao	Yang xiaoxu	Liu jiaying