

## Single 2-Input NAND Gate with Open Drain Output

### General Description


The ET74HC1G38 is a high-performance single 2-input NAND gate with open drain output operating from a 2V to 6V supply. This device is fabricated with advanced CMOS technology to achieve ultra-high speed with high output drive.

### Features

- Designed for 2V to 6V  $V_{CC}$  Operation
- Over-voltage Tolerant Inputs Accept Voltages to 6V
- 5.2mA Output Sink Capability
- Near Zero Static Supply Current Substantially Reduces System Power Requirements
- These Devices are Pb-Free and RoHS Compliant
- ESD Protection Complies with JESD22 Standard
  - HBM:  $\pm 2000V$  Pass (JEDEC JS-001)
  - CDM:  $\pm 1000V$  Pass (JEDEC JS-002)
- Latch-up Performance Exceeds  $\pm 100mA$  per JEDEC JESD78F
- Part No. and Package Information

| Part No.    | Package                        | Packing Option         | MSL |
|-------------|--------------------------------|------------------------|-----|
| ET74HC1G38  | SC70-5 (1.3mm $\times$ 2.1mm)  | Tape and Reel, 3K/Reel | 1   |
| ET74HC1G38T | SOT23-5 (1.6mm $\times$ 2.9mm) | Tape and Reel, 3K/Reel | 3   |
| ET74HC1G38Y | DFN6 (1.0mm $\times$ 1.5mm)    | Tape and Reel, 3K/Reel | 1   |

### Pin Configuration



# ET74HC1G38

## Pin Function


SC70-5/SOT23-5

| Pin No. | Pin Name | Function       |
|---------|----------|----------------|
| 1       | A        | Input A        |
| 2       | B        | Input B        |
| 3       | GND      | Ground         |
| 4       | Y        | Output         |
| 5       | VCC      | Supply Voltage |

DFN6

| Pin No. | Pin Name | Function       |
|---------|----------|----------------|
| 1       | A        | Input A        |
| 2       | B        | Input B        |
| 3       | GND      | Ground         |
| 4       | Y        | Output         |
| 5       | NC       | No Connect     |
| 6       | VCC      | Supply Voltage |

## Block Diagram



## Functional Table

| Input |   | Output |
|-------|---|--------|
| A     | B | Y      |
| L     | L | Z      |
| L     | H | Z      |
| H     | L | Z      |
| H     | H | L      |

# ET74HC1G38

## Absolute Maximum Ratings

| Symbol           | Parameter                                                                  |                                     | Value                         | Unit |
|------------------|----------------------------------------------------------------------------|-------------------------------------|-------------------------------|------|
| V <sub>CC</sub>  | DC Supply Voltage (VCC Pin)                                                |                                     | -0.5 to 7.0                   | V    |
| I <sub>IK</sub>  | DC Input Diode Current, V <sub>I</sub> < GND                               |                                     | ±20                           | mA   |
| V <sub>I</sub>   | DC Input Voltage <sup>(1)</sup>                                            |                                     | -0.5 ≤ V <sub>I</sub> ≤ 7.0   | V    |
| I <sub>OK</sub>  | DC Output Diode Current, V <sub>O</sub> < GND                              |                                     | ±20                           | mA   |
| V <sub>O</sub>   | DC Output Voltage Output in Higher or Low State                            |                                     | -0.5 to V <sub>CC</sub> + 0.5 | V    |
| I <sub>O</sub>   | DC Output Sink Current, V <sub>O</sub> = -0.5V to V <sub>CC</sub> + 0.5V   |                                     | 25                            | mA   |
| I <sub>CC</sub>  | DC Supply Current per Supply Pin                                           |                                     | 50                            | mA   |
| I <sub>GND</sub> | DC Ground Current per Supply Pin                                           |                                     | -50                           | mA   |
| T <sub>J</sub>   | Max Junction Temperature                                                   |                                     | 150                           | °C   |
| T <sub>STG</sub> | Storage Temperature Range                                                  |                                     | -65 to 150                    | °C   |
| V <sub>ESD</sub> | ESD Classification                                                         | Human Body Model <sup>(2)</sup>     | ±2000                         | V    |
|                  |                                                                            | Charged Device Model <sup>(3)</sup> | ±1000                         |      |
| I <sub>LU</sub>  | Max Latch Up Current Above V <sub>CC</sub> and GND at 125°C <sup>(4)</sup> |                                     | ±100                          | mA   |

Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.

**Note1:** I<sub>O</sub> absolute maximum rating must be observed.

**Note2:** HBM tested per JEDEC JS-001;

**Note3:** CDM tested per JEDEC JS-002;

**Note4:** Latch up Current Maximum Rating tested per JEDEC JESD78F.

## Thermal Characteristics

| Symbol           | Package | Ratings                                                      | Value | Unit |
|------------------|---------|--------------------------------------------------------------|-------|------|
| R <sub>θJA</sub> | SC70-5  | Thermal Characteristics, Thermal Resistance, Junction-to-Air | 280   | °C/W |
|                  | SOT23-5 |                                                              | 180   |      |
|                  | DFN6    |                                                              | 440   |      |
| P <sub>D</sub>   | SC70-5  | Power Dissipation in Still Air at 85°C                       | 230   | mW   |
|                  | SOT23-5 |                                                              | 360   |      |
|                  | DFN6    |                                                              | 150   |      |

## Recommended Operating Conditions

| Symbol                          | Parameter                             |                        | Min | Max             | Unit |
|---------------------------------|---------------------------------------|------------------------|-----|-----------------|------|
| V <sub>CC</sub>                 | DC Supply Voltage Operating           |                        | 2   | 6               | V    |
| V <sub>I</sub>                  | DC Input Voltage                      |                        | 0   | V <sub>CC</sub> | V    |
| V <sub>O</sub>                  | DC Output Voltage (High or Low State) |                        | 0   | V <sub>CC</sub> | V    |
| T <sub>A</sub>                  | Operating Temperature Range           |                        | -40 | 125             | °C   |
| t <sub>r</sub> , t <sub>f</sub> | Input Rise and Fall Time              | V <sub>CC</sub> = 2.0V |     | 625             | ns/V |
|                                 |                                       | V <sub>CC</sub> = 4.5V |     | 139             |      |
|                                 |                                       | V <sub>CC</sub> = 6.0V |     | 83              |      |

# ET74HC1G38

## Electrical Characteristics

### DC Electrical Characteristics

| Symbol           | Parameter                 | Condition                                  | V <sub>CC</sub> (V) | T <sub>A</sub> = 25°C |                 |      | -40°C ≤ T <sub>A</sub> ≤ 125°C |      | Unit |
|------------------|---------------------------|--------------------------------------------|---------------------|-----------------------|-----------------|------|--------------------------------|------|------|
|                  |                           |                                            |                     | Min                   | Typ             | Max  | Min                            | Max  |      |
| V <sub>IH</sub>  | High-Level Input Voltage  |                                            | 2.0                 | 1.5                   |                 |      | 1.5                            |      | V    |
|                  |                           |                                            | 4.5                 | 3.15                  |                 |      | 3.15                           |      |      |
|                  |                           |                                            | 6.0                 | 4.2                   |                 |      | 4.2                            |      |      |
| V <sub>IL</sub>  | Low-Level Input Voltage   |                                            | 2.0                 |                       |                 | 0.5  |                                | 0.5  | V    |
|                  |                           |                                            | 4.5                 |                       |                 | 1.35 |                                | 1.35 |      |
|                  |                           |                                            | 6.0                 |                       |                 | 1.8  |                                | 1.8  |      |
| V <sub>OL</sub>  | Low-Level Output Voltage  | I <sub>OL</sub> = 20μA                     | 2~6                 | V <sub>CC</sub> - 0.1 | V <sub>CC</sub> |      | V <sub>CC</sub> - 0.1          |      | V    |
|                  |                           | I <sub>OL</sub> = 4mA                      | 4.5                 | 4.13                  | 4.32            |      | 3.7                            |      |      |
|                  |                           | I <sub>OL</sub> = 5.2mA                    | 6.0                 | 5.63                  | 5.81            |      | 5.2                            |      |      |
| I <sub>I</sub>   | Input Leakage Current     | V <sub>I</sub> = 6V or GND                 | 0~6                 |                       | ±0.1            |      |                                | ±1.0 | μA   |
| I <sub>OFF</sub> | Power Off Leakage Current | V <sub>I</sub> = 6V or V <sub>O</sub> = 6V | 0                   |                       |                 | 1    |                                | 10   | μA   |
| I <sub>CC</sub>  | Quiescent Supply Current  | V <sub>I</sub> = 6V or GND                 | 6                   |                       |                 | 1    |                                | 10   | μA   |

# ET74HC1G38

## AC Electrical Characteristics

| Symbol           | Parameter         | Condition                                | V <sub>CC</sub> (V) | T <sub>A</sub> = 25°C |     |     | -40°C ≤ T <sub>A</sub> ≤ 125°C |     | Unit |
|------------------|-------------------|------------------------------------------|---------------------|-----------------------|-----|-----|--------------------------------|-----|------|
|                  |                   |                                          |                     | Min                   | Typ | Max | Min                            | Max |      |
| t <sub>PLZ</sub> | Propagation Delay | xA to xY;<br>See <a href="#">Figure3</a> | 2.0                 |                       | 13  | 33  |                                | 39  | ns   |
|                  |                   |                                          | 4.5                 |                       | 4.3 | 4.9 |                                | 5.6 |      |
| t <sub>PZL</sub> |                   |                                          | 6.0                 |                       | 3.9 | 4.4 |                                | 4.9 |      |

## Capacitance Characteristics

| Symbol          | Parameter                                    | Condition                                                             | Typ | Unit |
|-----------------|----------------------------------------------|-----------------------------------------------------------------------|-----|------|
| C <sub>IN</sub> | Input Capacitance                            | V <sub>CC</sub> = 6V, V <sub>I</sub> = 0 V or V <sub>CC</sub>         | 5   | pF   |
| C <sub>PD</sub> | Power Dissipation Capacitance <sup>(5)</sup> | 10MHz, V <sub>CC</sub> = 3.3V, V <sub>I</sub> = 0V or V <sub>CC</sub> | 25  | pF   |

**Note5:** C<sub>PD</sub> is used to determine the dynamic power dissipation (P<sub>D</sub> in μW).

$$P_D = C_{PD} \times V_{CC}^2 \times f_i \times N + \Sigma(C_L \times V_{CC}^2 \times f_o) \text{ where:}$$

f<sub>i</sub> = input frequency in MHz;

f<sub>o</sub> = output frequency in MHz;


C<sub>L</sub> = output load capacitance in pF;

V<sub>CC</sub> = supply voltage in V;

N = number of inputs switching;

Σ(C<sub>L</sub> × V<sub>CC</sub><sup>2</sup> × f<sub>o</sub>) = sum of outputs.

## Test Waveform



Measurement points are given in [Table1](#).

V<sub>O\_L</sub> is typical output voltage levels that occur with the output load.


Figure3. Input xA to Output xY Propagation Delay Times

# ET74HC1G38

Table1. Measurement Points

| Supply Voltage | Input               | Output              |                 |
|----------------|---------------------|---------------------|-----------------|
| $V_{CC}$       | $V_M$               | $V_M$               | $V_X$           |
| 2V             | $0.5 \times V_{CC}$ | $0.5 \times V_{CC}$ | $V_{OL} + 0.3V$ |
| 4.5V           | $0.5 \times V_{CC}$ | $0.5 \times V_{CC}$ | $V_{OL} + 0.3V$ |
| 6V             | $0.5 \times V_{CC}$ | $0.5 \times V_{CC}$ | $V_{OL} + 0.3V$ |

## Test Circuit



Measurement points are given in [Table2](#).

Definitions test circuit:

$R_L$  = Load resistance;

$C_L$  = Load capacitance including jig and probe capacitance;

$R_T$  = Termination resistance should be equal to output impedance  $Z_O$  of the pulse generator;

$V_{EXT}$  = External voltage for measuring switching times.

Figure4. Test Circuit for Measuring Switching Times


Table2. Test Data

| Supply Voltage | Input    |             | Load  |             | $V_{EXT}$          |
|----------------|----------|-------------|-------|-------------|--------------------|
| $V_{CC}$       | $V_I$    | $t_r = t_f$ | $C_L$ | $R_L$       | $t_{PZL}, t_{PLZ}$ |
| 2V             | $V_{CC}$ | 3.0ns       | 50pF  | 1k $\Omega$ | $2 \times V_{CC}$  |
| 4.5V           | $V_{CC}$ | 3.0ns       | 50pF  | 1k $\Omega$ | $2 \times V_{CC}$  |
| 6V             | $V_{CC}$ | 3.0ns       | 50pF  | 1k $\Omega$ | $2 \times V_{CC}$  |

# ET74HC1G38

## Package Dimension

SC70-5 (1.3mm × 2.1mm)




### COMMON DIMENSIONS

(Unit: mm)

| SYMBOL | MIN     | NOM  | MAX  |
|--------|---------|------|------|
| A      | -       | -    | 1.10 |
| A1     | 0.00    | -    | 0.15 |
| b      | 0.15    | -    | 0.35 |
| c      | 0.08    | -    | 0.20 |
| D      | 2.00    | 2.10 | 2.30 |
| e      | 0.65BSC |      |      |
| e1     | 1.30BSC |      |      |
| E      | 2.15    | 2.30 | 2.50 |
| E1     | 1.15    | 1.30 | 1.45 |
| L      | 0.50REF |      |      |
| L1     | 0.33REF |      |      |

# ET74HC1G38

SOT23-5 (1.6mm × 2.9mm)



## COMMON DIMENSIONS


(Unit: mm)

| SYMBOL | MIN     | NOM  | MAX  |
|--------|---------|------|------|
| A      | -       | -    | 1.45 |
| A1     | 0.00    | -    | 0.15 |
| b      | 0.28    | 0.35 | 0.50 |
| c      | 0.08    | 0.15 | 0.22 |
| D      | 2.75    | 2.9  | 3.05 |
| e      | 0.90    | 0.95 | 1.00 |
| e1     | 1.80    | 1.90 | 2.00 |
| E      | 2.60    | 2.80 | 3.00 |
| E1     | 1.45    | 1.6  | 1.75 |
| L      | 0.60REF |      |      |
| L1     | 0.30    | 0.45 | 0.60 |



# ET74HC1G38

DFN6 (1.0mm × 1.5mm)




COMMON DIMENSIONS  
(Unit: mm)

| SYMBOL | MIN     | NOM  | MAX  |
|--------|---------|------|------|
| A      | 0.50    | --   | 0.60 |
| A1     | 0.00    | 0.02 | 0.05 |
| A3     | 0.10REF |      |      |
| b      | 0.15    | 0.20 | 0.25 |
| D      | 0.90    | 1.00 | 1.10 |
| E      | 1.40    | 1.50 | 1.60 |
| e      | 0.50BSC |      |      |
| K      | 0.30REF |      |      |
| K1     | 0.25REF |      |      |
| L      | 0.35    | 0.40 | 0.45 |
| L1     | 0.30    | 0.35 | 0.40 |


# ET74HC1G38

## Tape Information


SC70-5 (1.3mm × 2.1mm)



SOT23-5 (1.6mm × 2.9mm)



DFN6 (1.0mm × 1.5mm)



# ET74HC1G38

## Marking Information

|                                                                                                             |                                                                                                                           |
|-------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------|
| <div><div>1G38X</div><div></div></div> <div>ET74HC1G38<br/>1G38 = Part Number<br/>X = Tracking Number</div> | <div><div>C138<br/>XXXXX</div><div></div></div> <div>ET74HC1G38T<br/>C138 = Part Number<br/>XXXXX = Tracking Number</div> |
|-------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------|

## Revision History and Checking Table

| Version | Date       | Revision Item    | Modifier | Function & Spec Checking | Package & Tape Checking |
|---------|------------|------------------|----------|--------------------------|-------------------------|
| 1.0     | 2026-04-03 | Official Version | Xu tao   | Yang xiaoxu              | Liu jiaying             |