

Single Inverter with Open Drain Output

General Description

The ET74HCT1G06 is a high-performance single inverter with open drain outputs operating from a 4.5V to 5.5V supply. The Output stage is open drain with Over Voltage Tolerance. This allows the ET74HCT1G06 to be used to interface 5.0V circuits to circuits of any voltage between 0 and 6.5V.

Features

- Designed for 4.5V to 5.5V V_{CC} Operation
- 8mA Output Sink Capability
- Over-voltage Tolerant Inputs Accept Voltages to 5.5V
- These Devices are Pb-Free, Halogen Free/BFR Free and RoHS Compliant.
- ESD Protection Complies with JESD22 Standard
 - HBM: $\pm 4000V$ Pass (JEDEC JS-001)
 - CDM: $\pm 1000V$ Pass (JEDEC JS-002)
- Latch-up Performance Exceeds $\pm 100mA$ per JEDEC JESD78F
- Part No. and Package Information

Part No.	Package	Packing Option	MSL
ET74HCT1G06	SC70-5 (1.3mm $\times$ 2.1mm)	Tape and Reel, 3K/Reel	1
ET74HCT1G06T	SOT23-5 (1.6mm $\times$ 2.9mm)	Tape and Reel, 3K/Reel	3
ET74HCT1G06Y	DFN6 (1.0mm $\times$ 1.5mm)	Tape and Reel, 3K/Reel	1

Pin configuration




Figure1. Pin Configuration

ET74HCT1G06

Pin Function

SC70-5/ SOT23-5

Pin No.	Pin Name	Function
1	NC	No Connect
2	A	Input
3	GND	Ground
4	Y	Output
5	VCC	Supply Voltage

DFN6

Pin No.	Pin Name	Function
1	NC	No Connect
2	A	Input
3	GND	Ground
4	Y	Output
5	NC	No Connect
6	VCC	Supply Voltage

Block Diagram




Figure2. Logic Symbol

Function Table

Input A	Output Y
L	Z
H	L

ET74HCT1G06

Absolute Maximum Ratings

Symbol	Parameter		Value	Unit
V _{CC}	DC Supply Voltage (VCC Pin)		-0.5 to 7.0	V
V _I	DC Input Voltage ⁽¹⁾		-0.5 ≤ V _I ≤ 7.0	V
V _O	DC Output Voltage Output in Higher or Low State		-0.5 to V _{CC} + 0.5	V
I _{IK}	DC Input Diode Current, V _I < GND		-50	mA
I _{OK}	DC Output Diode Current, V _O < GND, V _O > V _{CC}		±50	mA
I _O	DC Output Sink Current		±50	mA
I _{CC}	DC Supply Current Per Supply Pin		100	mA
I _{GND}	DC Ground Current Per Supply Pin		-100	mA
T _{STG}	Storage Temperature Range		-65 to 150	°C
T _L	Lead Temperature, Soldering 10 Seconds		260	°C
T _J	Max Junction Temperature		150	°C
V _{ESD}	ESD Classification	Human Body Model ⁽²⁾	±4000	V
		Charged Device Model ⁽³⁾	±1000	
I _{LU}	Max Latch Up Current Above V _{CC} and GND at 125°C ⁽⁴⁾		±100	mA

Stresses exceeding those listed in this table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.

Note1: I_O absolute maximum rating must be observed.

Note2: HBM tested per JEDEC JS-001;

Note3: CDM tested per JEDEC JS-002;

Note4: Latch Up Current Maximum Rating tested per JEDEC JESD78F.

Thermal Characteristics

Symbol	Package	Ratings	Value	Unit
R _{θJA}	SC70-5	Thermal Characteristics, Thermal Resistance, Junction-to-Air	300	°C/W
	SOT23-5		250	
	DFN6		440	
P _D	SC70-5	Power Dissipation in Still Air at 85°C	215	mW
	SOT23-5		260	
	DFN6		150	

Recommended Operating Conditions

Symbol	Parameter	Min	Max	Unit
V _{CC}	DC Supply Voltage	4.5	5.5	V
V _I	DC Input Voltage	0	V _{CC}	V
V _O	DC Output Voltage (High or Low State)	0	V _{CC}	V
T _A	Operating Temperature Range	-40	125	°C

ET74HCT1G06

Electrical Characteristics

DC Electrical Characteristics

($R_{PULL} = 1k\Omega$, Connect V_O to V_{CC})

Symbol	Parameter	Condition	$V_{CC}(V)$	$T_A = 25^\circ C$			$-40^\circ C \leq T_A \leq 125^\circ C$		Unit
				Min	Typ	Max	Min	Max	
V_{IH}	High-Level Input Voltage		4.5	2			2		V
			5.5	2			2		
V_{IL}	Low-Level Input Voltage		4.5			0.8		0.8	V
			5.5			0.8		0.8	
V_{OL}	Low-Level Output Voltage	$I_{OL} = 50\mu A$	4.5			0.1		0.1	V
		$I_{OL} = 8mA$				0.36		0.44	
I_I	Input Leakage Current	$V_I = 5.5V$ or GND	0~5.5			± 0.1		± 1.0	μA
I_{OFF}	Power Off Leakage Current	$V_I = 5.5V$ or $V_O = 5.5V$	0			1		10	μA
I_{CC}	Quiescent Supply Current	$V_I = 5.5V$ or GND	5.5			1		10	μA

AC Electrical Characteristics

$t_r = t_f = 3ns$, $R_1 = R_L = 1k\Omega$;

Symbol	Parameter	Condition	$V_{CC}(V)$	$T_A = 25^\circ C$			$-40^\circ C \leq T_A \leq 125^\circ C$		Unit
				Min	Typ	Max	Min	Max	
t_{PLZ}	Propagation Delay (Figure 3 and 4)	$C_L = 50pF$	4.5		12.5	23.5		27.5	ns
t_{PZL}		$C_L = 15pF$	5.0		10.5				

ET74HCT1G06

Capacitance Characteristics

Symbol	Parameter	Condition	Typ	Unit
C_{IN}	Input Capacitance	$V_{CC} = 5.5V, V_I = 0V \text{ or } V_{CC}$	2.8	pF
C_{PD}	Power Dissipation Capacitance ⁽⁵⁾	10MHz, $V_{CC} = 5V, V_I = 0V \text{ or } V_{CC}$	3	pF

Note5: C_{PD} is used to determine the dynamic power dissipation (P_D in μW).

$$P_D = C_{PD} \times V_{CC}^2 \times f_i \times N + \Sigma(C_L \times V_{CC}^2 \times f_o) \text{ where:}$$

f_i = input frequency in MHz;

f_o = output frequency in MHz;

C_L = output load capacitance in pF;

V_{CC} = supply voltage in V;

N = number of inputs switching;

$\Sigma(C_L \times V_{CC}^2 \times f_o)$ = sum of outputs.

AC Test Circuit





Figure3. Switching Waveform




$R_T = 50\Omega(\text{Typ})$
Figure4. Test Circuit

ET74HCT1G06

Package Dimension

SC70-5 (1.3mm × 2.1mm)




COMMON DIMENSIONS

(Unit: mm)

SYMBOL	MIN	NOM	MAX
A	-	-	1.10
A1	0.00	-	0.15
b	0.15	-	0.35
c	0.08	-	0.20
D	2.00	2.10	2.30
e	0.65BSC		
e1	1.30BSC		
E	2.15	2.30	2.50
E1	1.15	1.30	1.45
L	0.50REF		
L1	0.33REF		

ET74HCT1G06

SOT23-5 (1.6mm × 2.9mm)




COMMON DIMENSIONS

(Unit: mm)

SYMBOL	MIN	NOM	MAX
A	-	-	1.45
A1	0.00	-	0.15
b	0.28	0.35	0.50
c	0.08	0.15	0.22
D	2.75	2.9	3.05
e	0.90	0.95	1.00
e1	1.80	1.90	2.00
E	2.60	2.80	3.00
E1	1.45	1.6	1.75
L	0.60REF		
L1	0.30	0.45	0.60

ET74HCT1G06

DFN6 (1.0mm × 1.5mm)




COMMON DIMENSIONS
(Unit: mm)

SYMBOL	MIN	NOM	MAX
A	0.50	--	0.60
A1	0.00	0.02	0.05
A3	0.10REF		
b	0.15	0.20	0.25
D	0.90	1.00	1.10
E	1.40	1.50	1.60
e	0.50BSC		
K	0.30REF		
K1	0.25REF		
L	0.35	0.40	0.45
L1	0.30	0.35	0.40


ET74HCT1G06

Tape Information


SC70-5 (1.3mm × 2.1mm)



SOT23-5 (1.6mm × 2.9mm)





DFN6 (1.0mm × 1.5mm)



ET74HCT1G06

Marking Information

	
ET74HCT1G06	ET74HCT1G06T
T106 = Part Number	T106 = Part Number
X = Tracking Number	XXXXX = Tracking Number

Revision History and Checking Table

Version	Date	Revision Item	Modifier	Function & Spec Checking	Package & Tape Checking
1.0	2025-10-28	Official Version	Wang anran	Yang xiaoxu	Liu jiaying
1.0.a	2025-12-25	Update Format	Xu tao	Yang xiaoxu	Liu jiaying