

Octal Buffers/Drivers With 3-State Outputs

General Description

The ET74HCT541 octal buffers/drivers is ideal for driving bus lines or buffer memory address registers. The device feature inputs and outputs on opposite sides of the package to facilitate printed circuit board layout.

The 3-state control gate is a 2-input AND gate with active-low inputs so that if either output-enable($\overline{OE}1$ or $\overline{OE}2$) input is high, all corresponding outputs are in the high-impedance state. The outputs provide non-inverted data when they are not in the high-impedance state.

To ensure the high-impedance state during power up or power down, $\overline{OE}$ should be tied to VCC through a pull-up resistor; the minimum value of the resistor is determined by the current-sinking capability of the driver.

Features

- Designed for 4.5V to 5.5V V_{CC} Operation
- Over-voltage Tolerant Inputs Accept Voltages to 5.5V
- ± 8 mA Balanced Output Sink and Source Capability
- Inputs are TTL Voltage Compatible
- ESD Protection Complies with JESD22 Standard
 - HBM: ± 2000 V Pass (JEDEC JS-001)
 - CDM: ± 1500 V Pass (JEDEC JS-002)
- Latch-up Performance Exceeds ± 200 mA per JEDEC JESD78F
- Part No. and Package Information


Part No.	Package	MSL
ET74HCT541V	TSSOP20 (6.5mm $\times$ 4.4mm)	3
ET74HCT541M	SOP20 (12.75mm $\times$ 7.5mm)	3

Applications

- Fully Compliant with Standards for Automotive Applications
- Combine Normal Power Signals from Multiple Power Rails

ET74HCT541

Pin Configuration



TSSOP20/SOP20

Figure1. Pin Configuration

Pin Function

TSSOP20/SOP20

Pin No.	Name	Description
1	$\overline{\text{OE}} 1$	Output Enable 1
2	A1	Input A1
3	A2	Input A2
4	A3	Input A3
5	A4	Input A4
6	A5	Input A5
7	A6	Input A6
8	A7	Input A7
9	A8	Input A8
10	GND	Ground
11	Y8	Output Y8
12	Y7	Output Y7
13	Y6	Output Y6
14	Y5	Output Y5
15	Y4	Output Y4
16	Y3	Output Y3
17	Y2	Output Y2
18	Y1	Output Y1
19	$\overline{\text{OE}} 2$	Output Enable 2
20	VCC	Power

ET74HCT541

Block Diagram




Figure2. Logic Symbol

Functional Table

Inputs			Output
$\overline{OE} 1$	$\overline{OE} 2$	A	Y
L	L	L	L
L	L	H	H
H	X	X	Z
X	H	X	Z

H = High voltage level ,

L = Low voltage level ,

X = Don't care ,

Z = High-impedance OFF-state.

ET74HCT541

Absolute Maximum Ratings

Symbol	Parameter		Value	Unit
V _{CC}	DC Supply Voltage (VCC Pin)		-0.5 to 6.5	V
V _I	DC Input Voltage ⁽¹⁾		-0.5 to 6.5	V
V _O	DC Output Voltage		-0.5 to V _{CC} + 0.5	V
I _{IK}	DC Input Diode Current, V _I < GND		-20	mA
I _{OK}	DC Output Diode Current, V _O < GND		-50	mA
I _O	DC Output Sink Current, V _O = 0V to V _{CC}		±35	mA
I _{CC}	DC Supply Current per Supply Pin		70	mA
I _{GND}	DC Ground Current per Supply Pin		-70	mA
T _J	Maximum Junction Temperature		150	°C
T _{STG}	Storage Temperature Range		-65 to 150	°C
V _{ESD}	ESD Classification	Human Body Model ⁽²⁾	±2000	V
		Charged Device Model ⁽³⁾	±1500	
I _{LU}	Max Latch Up Current Above V _{CC} and GND ⁽⁴⁾		±200	mA

Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.

Note1: I_O absolute maximum rating must be observed.

Note2: HBM tested per JEDEC JS-001;

Note3: CDM tested per JEDEC JS-002;

Note4: Latch up Current Maximum Rating tested per JEDEC JESD78F.

Recommended Operating Conditions

Symbol	Parameter	Min	Max	Unit
V _{CC}	Supply voltage	4.5	5.5	V
V _I	Input Voltage	0	V _{CC}	V
V _O	Output Voltage	0	V _{CC}	V
T _A	Operating Temperature Range	-40	125	°C

ET74HCT541

Electrical Characteristics

DC Electrical Characteristics

Symbol	Parameter	Condition	V _{CC} (V)	T _A = 25°C			-40°C ≤ T _A ≤ 125°C		Unit
				Min	Typ	Max	Min	Max	
V _{IH}	High-Level Input Voltage		4.5	2			2		V
			5.5	2			2		
V _{IL}	Low-Level Input Voltage		4.5			0.8		0.8	V
			5.5			0.8		0.8	
V _{OH}	High-Level Output Voltage	I _{OH} = -50uA	4.5	4.4	4.5		4.4		V
		I _{OH} = -8mA		3.94			3.8		
V _{OL}	Low-Level Output Voltage	I _{OL} = 50uA	4.5			0.1		0.1	V
		I _{OL} = 8mA				0.36		0.44	
I _I	Input Leakage Current	V _I = 5.5V or GND	0~5.5			±0.1		±1.0	uA
I _{OFF}	Power Off Leakage Current	V _I = 5.5V or V _O = 5.5V	0			1		10	uA
I _{CC}	Quiescent Supply Current	V _I = 5.5V or GND	5.5			1		10	uA

ET74HCT541

Switching Characteristics

$t_r = t_f = 3\text{ns}$

Symbol	Parameter	Condition	$V_{CC}(\text{V})$	$T_A = 25^\circ\text{C}$			$-40^\circ\text{C} \leq T_A \leq 125^\circ\text{C}$		Unit
				Min	Typ	Max	Min	Max	
t_{PLH} t_{PHL}	Propagation Delay From A to Y (Figure3 and 4)	$C_L = 15\text{pF}$	4.5		8.2	16		19	ns
		$C_L = 50\text{pF}$	5.0		7				
t_{PLH} t_{PHL}	Propagation Delay From $\overline{OE}$ to Y (Figure3 and 4)	$C_L = 15\text{pF}$	4.5		10	18		21	ns
		$C_L = 50\text{pF}$	5.0		8				
t_{PLH} t_{PHL}	Propagation Delay From $\overline{OE}$ to Y (Figure3 and 4)	$C_L = 15\text{pF}$	4.5		9	17		20	ns
		$C_L = 50\text{pF}$	5.0		7				

Capacitance Characteristics

Symbol	Parameter	Condition	Typ	Unit
C_I	Input Capacitance	$V_{CC} = 5\text{V}$, $V_I = 0\text{V}$ or V_{CC}	10	pF
C_{PD}	Power Dissipation Capacitance ⁽⁵⁾	10MHz, $V_{CC} = 5\text{V}$, $V_I = 0\text{V}$ or V_{CC}	12	pF

Note5: C_{PD} is used to determine the dynamic power dissipation (P_D in μW).

$$P_D = C_{PD} \times V_{CC}^2 \times f_i \times N + \Sigma(C_L \times V_{CC}^2 \times f_o) \text{ where:}$$

f_i = input frequency in MHz;

f_o = output frequency in MHz;

C_L = output load capacitance in pF;


V_{CC} = supply voltage in V;

N = number of inputs switching;

$\Sigma(C_L \times V_{CC}^2 \times f_o)$ = sum of outputs.

ET74HCT541

AC Test Circuit



TEST	S1
t_{PLH}/t_{PHL}	Open
t_{PLZ}/t_{PZL}	V_{LOAD}
t_{PHZ}/t_{PZH}	GND

Figure3. Test Circuit for Measuring Switching Times




Figure4. Input to Output Propagation Delay Times

NoteA: C_L includes probe and jig capacitance.

NoteB: Waveform 1 is for an output with internal conditions such that the output is low, except when disabled by the output control.

NoteC: Waveform 2 is for an output with internal conditions such that the output is high, except when disabled by the output control.

NoteD: All input pulses are supplied by generators having the following characteristics:

PRR $\leq$ 10MHz, $Z_O = 50\Omega$.

NoteE: The outputs are measured one at a time, with one transition per measurement.

NoteF: t_{PLZ} and t_{PHZ} are the same as t_{dis} .

NoteG: t_{PZL} and t_{PZH} are the same as t_{en} .


NoteH: t_{PLH} and t_{PHL} are the same as t_{pd} .

Notel: All parameters and waveforms are not applicable to all devices.

ET74HCT541

Package Dimension

TSSOP20 (6.5mm × 4.4mm)




COMMON DIMENSIONS

(Unit: mm)

SYMBOL	MIN	MAX
A	--	1.20
A1	0.05	0.15
b	0.19	0.30
c	0.15 REF	
D	6.40	6.60
E	6.20	6.60
E1	4.30	4.50
e	0.65BSC	
L	0.50	0.72
L2	0.25 REF	
θ	0°	8°

ET74HCT541

SOP20 (12.75mm × 7.5mm)



COMMON DIMENSIONS


(Unit: mm)

SYMBOL	MIN	MAX
A	--	2.65
A1	0.1	0.3
b	0.38	0.48
c	0.24	0.3
D	12.6	12.9
E	10.1	10.5
E1	7.4	7.6
e	1.27BSC	
L	0.6	1
L1	1.4REF	
θ	0°	8°


ET74HCT541

Tape Information

TSSOP20 (4.4mm × 6.5mm)



Marking Information



Revision History and Checking Table

Version	Date	Revision Item	Modifier	Function & Spec Checking	Package & Tape Checking
1.0	2026-07-20	Official Version	Wang anran	Yang xiaoxu	Liu jiaying